RTI PIKO 65

The powerful but compact RTI PIKO 65 is suitable for outdoor laser show applications at concerts, festivals, and other huge events with easy operation due to the built-in software and DMX control. The PIKO is equipped with the latest **RSL Semiconductor modules (RSL)** making it an amazing laser for beam shows and demanding graphic projections such as laser mapping or projections over long distances. The high-end performance is part of the PIKO's DNA and makes this possible due to the great performance combination of the semiconductor RSL & top scanners

- 65 W guaranteed power
- Advanced **RTI Semiconductor laser modules (RSL)** produce a perfect shaped beam profile for red & blue and green.
- **Maintenance free laser system**
- **RSL modules with no color misalignment**
- **New advanced sealed optical section with no color misalignment**
- Graphics capable - 38 kpps@8° ILDA scanners
- Full-color mixing
- Extremely sharp intense beams - low divergence
- **Integrated intelligent LaserAnimation Sollinger Mainboard** and ShowNET Laser Mainboard
- **Integrated Touch-Display** for adjustment of basic functions
- **Integrated network switch** for linking the control signal
- FB4-QS MAX optional integration
- Rugged tour-grade compact housing
- **360° Bracket with quick-lock system**

Carte mère ShowNET par défaut :

- Diverses options de contrôle :

DÉTAILS TECHNIQUES

Puissance garantie en sortie	65'000 mW
Puissance rouge	24'000 mW / 637 nm
Puissance vert	22'000 mW / 525 nm
Puissance bleu	30'000 mW / 455 nm
Caractéristiques de faisceaux	ca. 10 mm / <0.8 mrad
Scanners	38 kpps@8° ILDA
Angle de balayage max.	48°
Modes de fonctionnement	ILDA, DMX, LAN, ArtNet, streaming ILDA, carte SD intégrée, mode autonome
Classe laser	4

Sources laser	modules RTI RSL
Classe IP	IP54
Motifs de base	env. 120 effets (tunnel, vague, dents de scie, etc.)
Accessoires	connecteur interlock, clé, câble d'alimentation, mode d'emploi, licence logiciel Showeditor
Alimentation	85-250 V AC 50/60 Hz
Consommation électrique	2500 W
Dimensions	271 x 491 x 296 mm
Poids	28 kg
EAN / MPN	836215437

MODIFICATIONS DISPONIBLES:

*En raison de différentes technologies avancées de correction d'optiques utilisées dans nos systèmes, les puissances en sortie des modules peuvent légèrement différer des puissances annoncées pour le module correspondant. Divergence FWHM moyen selon le modèle.